

## CSB-4

### DESKTOP CONTACTLESS CARD READER/WRITER



SpringCard CSB4 is an ISO/IEC 14443 (A&B) and Mifare desktop contactless reader/writer. CSB4 is available in USB or serial version

#### KEY FEATURES

SpringCard CSB-4 reads and writes any Mifare or ISO/IEC 14443 (1, 2, 3 and 4) contactless card. T=CL ; protocol embedded in coupler's firmware allows fastest transactions.

CSB-4S is a serial device, easy to operate under any operating system.

CSB-4U comes with an USB driver (« virtual serial port ») for Windows and major OS. CSB-4U is directly powered by the USB interface.

#### SUPPORTED CONTACTLESS SMARTCARDS

CSB4 is compliant with ISO/IEC 14443 (A and B) standards. List of supported chips includes :

- NXP (Philips) : Mifare Classic and UltraLight, Desfire, ProX, SmartMX,
- ST MicroElectronics : SR176, SRiX...
- ASK CTS256B and CTS512B,
- MultOS or JavaCard T=CL cards,
- Calypso transportation cards,
- NFC mobile phones or other NFC-capable objects (tag emulation mode)

#### A FEW TYPICAL APPLICATIONS

- Mifare or Desfire read and write : private purse, RFID access control, loyalty card...
- Transportation ticket issuing (train, suburb, bus...)
- Electronical documents (e-passport, driving licence, ID card...)
- Strong authentication
- Digital signature through crypto-enabled T=CL cards...

#### SPRINGCARD & PRO ACTIVE

Established in 2000, Pro Active is an innovative provider of smartcard-related solutions, and one of the leaders on the contactless-reader market.

SpringCard distributes Pro Active's contact and contactless products worldwide, under a single brand name.

#### HEADQUARTERS, EUROPA SPRINGCARD

13 voie la Cardon  
Parc Gutenberg  
91120 Palaiseau  
FRANCE

Phone : +33 (0) 164 53 20 10  
Fax : +33 (0) 164 53 20 18

#### AMERICAS SPRINGCARD

964 Fifth Avenue  
Suite 235  
San Diego, CA 92101  
USA

Phone : +1 (619) 544 1450  
Fax : +1 (619) 573 6867

[www.springcard.com](http://www.springcard.com)

A PRO ACTIVE BRAND

**Pro  
Active**

## CSB-4

### DESKTOP CONTACTLESS CARD READER/WRITER



## TECHNICAL SPECIFICATIONS

### Contactless smartcard interface

Standards	ISO/IEC 14443 A and B, T=CL
RFID carrier	13.56 MHz
Operating distance	up to 8 cm depending on card and on environment
Card baud rate	106, 212 or 424 kbit/s
Supported cards (partial list) : <ul style="list-style-type: none"> <li>▪ NXP (Philips) Mifare Classic &amp; UltraLight</li> <li>▪ NXP (Philips) Desfire, SmartMX, ProX</li> <li>▪ Infineon SLE66 family</li> <li>▪ ST MicroElectronics SR, SRI, SRIX families</li> <li>▪ ASK CTS256/CTS512</li> <li>▪ Calypso (CD97, CD21, GTML...)<sup>1</sup></li> </ul> And virtually any ISO/IEC 14443 A or B compliant smartcard.	

<sup>1</sup> Calypso card operation is subject to an extra license fee. Contact us for information.

### CSB4-U (USB)

USB virtual serial comm. port or serial port	
Power supply	Bus powered (≈250mA under 5V)
Drivers	Windows, Windows CE, Linux
API	SpringProx API compliant with other Springcard contactless products

### CSB4-S (Serial)

Standard RS-232 interface (DB9 - RX/TX/GND)	
Power requirement	7.5 to 12V DC, 500mA International power adaptor provided
API	SpringProx API compliant with other Springcard contactless products

### Hardware specifications<sup>2</sup>

Status indicator	3 LEDs (red, yellow, green)
Dimensions (LxWxH)	146 x 92 x 20 mm
Housing material	ABS-94HB (self extinguishing UL94)
Weight	≈ 250g
USB or serial cable	≈ 1,80 m

### Environment and safety

Operating temperature	0 → +45°C
Storage temperature	-40 → +85°C
MTBF	500 000 hours
CE mark	EN50082 / EN55022 class B
Other standards	RoHS

<sup>2</sup> Note that CSB6 board may be sold without housing, for OEM integration

## ORDER CODES

PART #	Description
CSB4.3U	USB desktop contactless reader/writer
CSB4.3S	serial desktop contactless reader/writer

### PRECAUTIONS FOR INSTALLATION

This device is a contactless reader; it uses inductive coupling (magnetic field) to power the cards and communicate with them. Precaution must be taken to keep the reader far from any source of perturbation (e.g. other readers, computers...). Installing the reader near a metal surface (aluminium or steel plate...) will lead to shorter operating distance and increased power consumption. SpringCard has a long experience installing contactless couplers in various kind of devices. Do not hesitate to contact us if you need any assistance.

Information in this document is subject to change without notice.

Copyright © PRO ACTIVE SAS 2008, all rights reserved.  
Reproduction without written permission of PRO ACTIVE is forbidden.  
SPRINGCARD, PRO ACTIVE, and both logos are registered trademarks of PRO ACTIVE SAS.  
All other trademarks are property of their respective owners.

PRO ACTIVE company with a capital of 227 000 €  
R.C.S. EVRY B 429 665 482  
N.A.F. 722 C  
VAT # : FR 27 429 665 482  
France

[www.springcard.com](http://www.springcard.com)

A PRO ACTIVE BRAND  
**Pro Active**